

### /DC quick connector-1pin

Model: LAS-602B-1P  
Housing: PC  
Contact: phosphor copper  
Specification: 6A 250V T85 (ICE)  
6A 125V (UL)  
Flammability: UL94V-2  
Wire range : 0.34-1.0mm<sup>2</sup>/22-16AWG

Certification:   



### /quick connector

Model: LAS-603  
Housing: PC  
Contact: phosphor copper+stainelss steel  
Specification: 10A 250V T40 (CE) 10A 125V T80 (UL)  
Flammability: UL94V-2  
Wire range: 16-18AWG / 0.75-1.0mm<sup>2</sup>

Certification:  



### /DC quick connector-2pins

Model: LAS-602B-2P  
Housing: PC  
Contact: phosphor copper  
Specification: 6A 250V T85 (ICE)  
6A 125V (UL)

Flammability: UL94V-2  
Wire range: 0.34-1.0mm<sup>2</sup>/22-16AWG

Certification:   



### /quick connector

Model: LAS-606  
Housing: PA  
Contact: phosphor copper  
Specification: 6A 300V T80/T125  
Flammability: UL94V-2/UL94V-2/0  
Wire range: 18-22AWG

Certification: 



### /DC quick connector-3pins

Model: LAS-602B-3P  
Housing: PC  
Contact: phosphor copper  
Specification: 6A 250V T85 (ICE)  
6A 125V (UL)

Flammability: UL94V-2  
Wire range : 0.34-1.0mm<sup>2</sup>/22-16AWG

Certification:   



### /quick connector

Model: LAS-616  
Housing: PA  
Contact : phosphor copper+steel sheet  
Specification : 6A 125V T115  
Flammability: UL94V-2  
Wire range: 16-22AWG

Certification: 

