



LiGHT & SMART



2.5mm²/ Mini wire connector 2.5mm²

Model: LAS-261
 Housing: 2.5mm²
 copper+stainless steel
 Specification: 24A 450V (ICEC)
 Flammability: UL94V-2
 Wire range: 0.5-2.5mm² rigid wire
 0.5-1.5mm² stranded wire

Certification:     

4mm²/Quick terminal block connector

Model: LAS-262
 20A/300V/20A/PC
 Contact/copper+stainless steel
 Specification: 20A 600V T105 (UL)
 32A 450V T85 (IEC)
 Flammability: UL94V -2
 Wire range: 24-12AWG / 0.2-4.0mm² rigid wire
 0.2-2.5mm² stranded wire

Certification:      



6mm²/Wire connector 6mm²

Model: LAS-266-2/3/5
 Housing: PA/PC
 Contact: copper+stainless steel
 Specification: 30A 600V T85(UL)
 41A 450V T105(IEC)
 Flammability: UL94 V-2
 Wire range: 20-10AWG/0.5-6.0mm²

Certification:     



2.5mm²/ Mini quickterminal blockconnector

Model: LAS-287-2/3
 Housing: PA/PC
 Contact: copper+stainless steel
 Specification: 450V T85
 Flammability: UL94V -2
 Wire range: 0.2-2.5mm²

Certification:     

4mm²/Quickterminal blockconnector

Model: LAS-281/282/283
 Housing: PA/PC Contact: copper+stainless steel
 Specification: 20A 300V T105 (UL)
 20A 600V T105 (LAS-281)
 32A 450V T85 (IEC)
 Flammability: UL94V -2
 Wire range: 20-12AWG / 0.5-4.0mm²

Certification:      



2.5mm²/Rigid wire connector

Model: LAS-252/253/254/255
 Housing: PC
 Contact: copper+stainless steel
 Specification: 24A 300V T105 (UL)
 24A 450V T110 (IEC)
 Flammability: UL 94V-2
 Wire range: 14-20AWG /0.5- -2. rigid wire /1.5- -2.5 stranded wire

Certification:      E497783



4mm²/Rigid wire connector 4mm²

Model: LAS-233-2/3/4/5, LAS-233A-6/8
 Housing: PC
 Contact: copper+stainless steel
 Specification: 30A 600V T85(UL)
 32A 450V T105(IEC)
 Flammability: UL94 V-2
 Wire range: 20-12AWG/0.5-4.0mm²
 rigid wire / soldering wire

Certification:     

