



/Quick plug type spring connector

Model: LAS-821/831/841/851
 Housing: PC+PA / PC+PP
 Contact: copper nickel
 Specification : 6A-24A 450V T110/T85 (IEC)
 15A 300V T115 (UL)
 20A 300V T110 (PSE)
 Flammability: 850°C/GWT 850°C
 Wire range: 0.5-2.5mm² / 20-14AWG (UL)
 Certification:



/Mini plug type spring connector

Model: LAS-8621/8631
 Housing: PC+PA/ PC+PP
 Contact: copper+stainless steel nickel
 Specification: 17.5A 450V T110/T85
 Flammability: 850°C/GWT 850°C Wire range:
 0.5-1.5mm²

Certification:



/Double plug type spring connector

Model: LAS-862/863/864/865
 Housing: PC+PA / PC+PP (CQC)
 Contact: copper nickel
 Specification: 6A-24A 450V T110/T85
 (CQC)

Flammability: 850°C/GWT 850°C
 Wire range: 0.5-2.5mm²

Certification:



/Slim plug type spring connector

Model: LAS-838 Series
 Housing: PC+PA/ PC+PP
 Contact: copper nickel
 Specification: 6A-24A 450V T110/T85
 (IEC) 15A 300V T115 (UL)

Flammability: 850°C/GWT 850°C
 Wire range: 0.5-2.5mm² / 20-14AWG (UL)

Certification:



/Quick plug type spring connector

Model: LAS-836
 Housing: PC+PA/ PC+PP
 Contact: copper nickel
 Specification: 6A-24A 450V T110/T85
 (IEC) 15A 300V T115 (UL)

Flammability: 850°C/GWT 850°C (UL)
 Wire range: 0.5-2.5mm² / 20-14AWG

Certification:

