





/Mini 1 in 1 out waterproof junction box



Model: LAS-5618
 Housing: PC
 Specification: 17.5A 450V -25°C -60°C
 Flammability: 850°C/GWT 850°C
 Wire outer diameter: 4-8.5mm
 Wire range: Max 1.5mm²
 IP grade: IP67
 Certification:  



/1 in 1 out waterproof junction box



Model: LAS-5718-A
 Housing: PA
 Specification: 17.5A 450V -25°C -60°C
 Flammability: 850°C/GWT 850°C
 Wire outer diameter: 4-8.5mm
 Wire range: Max 1.5mm²
 IP grade: IP65
 Certification:  

/1 in 2 out waterproof junction box



Model: LAS-5718-B
 Housing: PA
 Specification: 17.5A 450V -25°C -60°C
 Flammability: 850°C/GWT 850°C
 Wire outer diameter: 4-8.5mm
 Wire range: Max 1.5mm²
 IP grade: IP65
 Certification:  

/2 in 2 out waterproof junction box



Model: LAS-5818-A
 Housing: PC
 Specification: 24A 450V -25°C -60°C
 Flammability: 850°C/GWT 850°C
 Wire outer diameter: 5-10mm
 Wire range: Max 2.5mm²
 IP grade: IP68
 Certification:  

/1 in 2 out waterproof junction box



Model: LAS-5818-B
 Housing: PC
 Specification: 24A 450V -25°C -60°C
 Flammability: 850°C/GWT 850°C
 Wire outer diameter: 5-10mm
 Wire range: Max 2.5mm²
 IP grade: IP68
 Certification: 