

Zhaga Book20

/Zhaga Book20 male-female with wire Poke-In Wire Termination

Model: LAS-682-M /LAS-682-M Socket (male);
LAS-682-L/LAS-682-L Plug (Female)
Rated Voltage: 250Vac
Rated Current: 22AWG MAX 3A /20AWG MAX 5A /18AWG
MAX 7A
Contact Resistance: 20mΩmax
Insulation Resistance: 500MΩ 500VDC
Dielectric Strength: 1.5KV/Imin
Operating Temperature Range: -40°C~+105°C
Environmental Compliance: RoHS 2.0
/Complies with RoHS 2.0

Zhaga Book20

/Zhaga Book20 male-female Poke-In Wire Termination

Model: LAS-683-M /LAS-683-M Socket (male)
LAS-683-L /LAS-683-L Plug (Female)
Rated Voltage: 250Vac
Rated Current: 22AWG MAX 3A
20AWG MAX
5A 18AWG
MAX 7A
Contact Resistance: 20mΩmax
Insulation Resistance: 500MΩ 500VDC
Dielectric Strength: 1.5KV/Imin
Operating Temperature Range: -40°C~+105°C
Environmental Compliance: RoHS 2.0
/Complies with RoHS 2.0

Zhaga Book20 SMT


/Zhaga Book20 SMT Wire Termination

Model: LAS-682-S SMT /LAS-682-S SMT Socket (male)
Rated Voltage: 250Vac
Rated Current: 22AWG MAX 3A /20AWG MAX 5A /18AWG MAX 7A
Contact Resistance: 20mΩmax
Insulation Resistance: 500MΩ 500VDC
Dielectric Strength: 1.5KV/Imin
Operating Temperature Range: -40°C~+105°C
Environmental Compliance: RoHS 2.0
/Complies with RoHS 2.0
Additional Requirements: F > 50N
/Pin Retention Force F > 50N

LAS-686



/ IP68 Wire Termination

Model: LAS-686-2P/3P
Rated Voltage: 250Vac Rated Current:
20AWG 4A 22AWG 3A 24AWG 2A
Operating Temperature Range: -40°C~+105°C
Wire range: 20-24AWG
Wiring: riveting process
certification:



/Flip lock waterproof junction box



Model: LAS-26H-2 /LAS-26H-2 Waterproof
box Housing: PP
IP Rating: IP68
Size: 42.2*30.4*16.2mm
Compatible Terminals: LAS-262/233-2P
Wire range: 0.5mm²-4mm²
/0.5mm²-4mm² Solid and Stranded Wires
Operating Temperature Range: -50°C to
85°C

Certification:  

/Flip lock waterproof junction box

Model: LAS-26H-3 LAS-26H-3 Waterproof
box
Housing: PP
IP Rating: IP68
Size: 42.2*36.2*16.2mm Compatible
Terminals: LAS-263/233-3P
Wire range: 0.5mm²-4mm² Solid and Stranded Wires

Operating Temperature Range: -50°C to
85°C

Certification:  

/Flip lock waterproof junction box

Model: LAS-26H-5 LAS-26H-5 Waterproof
box Housing: PP
IP Rating: IP68
Size: 42.2*47.8*16.2mm
Compatible Terminals: LAS-265/233-5P
Wire range: 0.5mm²-4mm²
/0.5mm²-4mm² Solid and Stranded Wires

Operating Temperature Range: -50°C to
85°C

Certification:  



LIGHT & SMART

300 Avenue de l'Europe 77310 Saint Fargeau Ponthierry
France
SIRET : 84973112000028 N° de TVA : FR04849731120
contact@lightandsmart.com www.lightandsmart.com