



## C-23-R-XP-M (MALE)/ C-23-R-XP-F (FEMALE)

Male & Female Self-locking Screwless Fast Wiring Connector  
(X = number of poles X = 2 or 3)

**Wiring Method:**

Screwless fast wiring

**Housing Material:** PA66

**Seal Ring Material:** Silicone Rubber

**Terminal Material:** Copper alloy

**IP Rating:** IP68

**Fire Rating:** UL94 V-0

**Rated Voltage:** 450V

**Rated Current:** 16A

**Wire Section:** 0.5~2.5mm<sup>2</sup>

**Outer Cable Diameter:** 5-9mm, 9-12mm

**Pluggable Life:** 1,500 times

**Ambient Temperature:** -40°C~105°C

**Warranty:** 3 Years

### Options

Number of Poles	 2Pin	 3Pin
Seal ring		
Cable range	5~9mm	9~12mm
Stripping length	11~14 mm	

### Packaging

Export Carton (L\*W\*H): 42\*30\*26cm

Quantity: 50pcs / PE PACK (Male & Female packed separately)

250 sets / CTN

Gross Weight: C-23-R-XP-MF-2P --- 13.3KGs

C-23-R-XP-MF-3P --- 13.8KGs



### Installation Illustration

