

C-25-R-XP-MF IP68 Waterproof Connector



C-25-R-XP-M/C-25-R-XP-F

Male & Female Self-locking Screwless Fast Wiring Connector

(X = number of poles X = 4 or 5)

Wiring Method:

Screwless fast wiring

Housing Material: PA66

Seal Ring Material: Silicone Rubber

Terminal Material: Copper alloy

IP Rating: IP68

Fire Rating: V0

Rated Voltage: 450V

Rated Current: 16A

Wire Section: 0.5~2.5mm²

Outer Cable Diameter: 5-9mm, 9-12mm, 10-14mm

Pluggable Life: 1,500 times

Ambient Temperature: -40°C~105°C

Warranty: 3 Years

Options

| Number of Poles | 4Pin | | 5Pin |
|------------------|----------|--------|---------|
| Seal ring | | | |
| Cable range | 5~9mm | 9~12mm | 10~14mm |
| Stripping length | 10~13 mm | | |

Packaging

Export Carton (L*W*H): 42*30*34cm

Quantity: 25pcs / PE PACK (Male & Female packed separately)

200 sets / CTN

Gross Weight: C-25-R-XP-MF-4P --- 14.5KGs

C-25-R-XP-MF-5P --- 14.9KGs



Installation Illustration

