

NEX.IVO

— by KGP Electronics GmbH —

2026



CONTENTS

NEXIVO – LED DRIVER PORTFOLIO 2026

01 – COMPANY

PAGE 04

OUR MISSION AND VISION

02 – TRACK 230V

PAGE 06

ON/OFF
HIGH EFFICIENCY
DALI / PUSH / NFC
INVISIBLE

PAGE 07

CCT / DIM ON BOARD
TRIAC
DALI 4 WIRE
ETL (120-277V)

03 – TRACK 24V / 48V

PAGE 08

POWER SUPPLY 48V
POWER SUPPLY 48V TB
PCB CONVERTER ON/OFF 24/48V
PCB CONVERTER DALI 24/48V

PAGE 09

PCB CONVERTER DT8 48V
POWER SUPPLY MICRO 48V
PCB CONVERTER MICRO ON/OFF 48V
PCB CONVERTER MICRO DALI 48V

04 – CC / CV – IOT

PAGE 10

CC COMPACT 1CH
CC COMPACT 2CH
CV COMPACT 1CH 24/48V
CV COMPACT 2CH 24/48V

PAGE 11

CC TRACK 230V 1CH / 2CH

05 – CC INDOOR

PAGE 12

COMPACT ON/OFF
COMPACT DALI
COMPACT HIGH EFFICIENCY
COMPACT HIGH EFFICIENCY DT8

PAGE 13

COMPACT DT8
COMPACT D4i
SLIM ON/OFF
SLIM DALI

PAGE 14

SLIM HIGH EFFICIENCY
SLIM MINI
ULTRA SLIM
SLIM DT8

PAGE 15

SLIM TRIAC
SLIM 0/1-10V

PAGE 16

MINI
TINY
ROUND

06 – CC LINEAR

PAGE 18

NON-SELV DALI
NON-SELV FLAT 11MM
NON-SELV
SELV ON/OFF

PAGE 19

SELV DALI
SELV FLAT 11MM ON/OFF
SELV FLAT 11MM DALI
SELV DT8

07 – CC UNI 100-240V

PAGE 20

TINY
SLIM
MINI
COMPACT

08 – CV INDOOR

PAGE 22

LINEAR ON/OFF 24V
LINEAR DALI 24V
LINEAR DT8 24V
LINEAR ON/OFF 48V

PAGE 23

LINEAR DALI 48V
LINEAR DT8 48V
COMPACT ON/OFF
COMPACT DALI

PAGE 24

ROUND 12/24/48V
LINEAR 24V
COMPACT TRIAC
SLIM 24/48V

09 – CC / CV OUTDOOR

PAGE 26

CC COMPACT ON/OFF
CC COMPACT DALI
CV SLIM ON/OFF 24V
CV SLIM DALI 24V

PAGE 27

CV SLIM ON/OFF 48V
CV SLIM DALI 48V
COMPACT UNI 12/24V

10 – CONTACT

PAGE 28

COMPANY DETAILS
CONTACT INFORMATION

OUR MISSION AND VISION

At NEXIVO by KGP Electronics GmbH, we believe that innovation in lighting begins with intelligent power solutions. With more than 40 years of expertise in the lighting and LED driver industry, we develop high-performance, reliable and future-oriented driver technologies tailored to the demands of the European market.

Our mission is to combine technical precision, flexibility and efficiency into products that empower luminaire manufacturers to create outstanding lighting solutions.

We focus on advanced driver concepts – from compact and ultra-slim indoor solutions to high-efficiency linear and track systems, including DALI, DT8, NFC and IoT integration. Every product is designed to deliver maximum performance, long-term stability and seamless system compatibility.

Our vision is to be more than a supplier.

We aim to be a trusted technology partner – supporting our customers with engineering competence, short lead times through local warehousing in Germany, and customized solutions when standard products are not enough.

Innovation drives us.

Quality defines us.

Partnership strengthens us.

NEXIVO

Next Innovations by KGP Electronics GmbH



TRACK 230V

ON/OFF

Item	Power	Output	Efficiency	Power Factor	Dimensions
SC20W150-500CG4-NX	20W	20-40V	89%	0.92	123x31x43mm
SC30W200-700CG4-NX	30W	10-42V	91%	0.95	123x31x45mm
SC42W300-1050CG4-NX	42W	25-40V	92%	0.97	133x31x45mm
SC60W1100-1400CG4-NX	60W	25-40V	89%	0.97	218x31x45mm
SC84W300-1050CG4-NX	84W	10-42V	86%	0.97	312x31x45mm

CC CE EAC UK CA RIPLE FREE IP20



HIGH EFFICIENCY

Item	Power	Output	Efficiency	Power Factor	Dimensions
SC30W350-700CG4-HE-NX	30W	25-40V	94%	0.95	148x31x45mm
SC42W700-1050CG4-HE-NX	42W	25-40V	94%	0.95	148x31x45mm

CC CE EAC UK CA RIPLE FREE IP20



DALI/PUSH | NFC

Item	Power	Output	Efficiency	Power Factor	Dimensions
SC28W150-700CG6-DALI-HE-NX	28W	10-42V	91%	0.95	218x31x45mm
SC42W300-1050CG6-DALI-HE-NX	42W	10-42V	92%	0.97	218x31x45mm
SC42W300-1050CG6-DT8-HE-NFC-NX	42W	10-42V	90%	0.97	238x31x45mm
SC60W1100-1400CG6-DALI-NX	60W	10-42V	89%	0.92	238x31x45mm

DALI CC CE EAC UK CA RIPLE FREE IP20



INVISIBLE

Item	Power	Output	Efficiency	Power Factor	Dimensions
SC42W300-1050CG4-INV-NX	42W	9-42V	90%	0.95	230x32x37mm
SC42W300-1050CG4-ED-NX	42W	10-42V	89%	0.97	213x32x37mm
SC30W150-700CG6-DALI-INV-NX	30W	10-42V	89%	0.95	270x32x37mm
SC42W300-1050CG6-DALI-ED-NX	42W	10-42V	88%	0.97	256x32x43mm

DALI CC CE EAC UK CA RIPLE FREE IP20



CCT/DIM ON BOARD

Item	Power	Output	Efficiency	Power Factor	Dimensions
SC42W300-1050CG4-DIM-NX	42W	10-42V	89%	0.96	178x31x45mm
SC42W300-1050CG4-CCT-NX	42W	10-42V	90%	0.96	178x31x45mm
SC42W300-1050CG4-CCT-DIM-NX	42W	10-42V	89%	0.96	178x31x45mm
SC42W300-1050CG4-TRIAC-CCT-NX	42W	10-42V	87%	0.93	218x31x45mm



TRIAC

Item	Power	Output	Efficiency	Power Factor	Dimensions
SC42W300-1050CG4-TRIAC-NX	42W	10-42V	87%	0.92	218x31x45mm



DALI 4 WIRE

Item	Power	Output	Efficiency	Power Factor	Dimensions
SC42W300-1050CG4-DALI-ED-NX	42W	10-42V	88%	0.97	178x32x43mm



ETL

Item	Power	Output	Efficiency	Power Factor	Dimensions
SC42W300-1050CG4-UNI-NX	42W	10-42V	90%	0.94	218x32x43mm



TRACK 24/48V

POWER SUPPLY 48V

Item	Power	Output	Efficiency	Power Factor	Dimensions
LV100W48VDC-NX	100W	48V	90%	0.95	297x16x19mm
LV100W48VDC-T-NX	100W	48V	90%	0.95	297x16x19mm
LV250W48VDC-NX	250W	48V	92%	0.95	268x22x43.5mm
LV250W48VDC-T-NX	250W	48V	92%	0.95	268x22x43.5mm

CABLE LENGTH OPTIONS: 0.3MTR/3.0MTR

CV CE UK CA RIPPLE FREE A IP20



POWER SUPPLY 48V TB

Item	Power	Output	Efficiency	Power Factor	Dimensions
LV100W48VDC-TB-NX	100W	48V	90%	0.95	371x22x44mm
LV250W48VDC-TB-NX	250W	48V	92%	0.95	371x22x44mm

CV CE UK CA RIPPLE FREE A IP20



PCB CONVERTER ON/OFF 24/48V

Item	Power	Input	Efficiency	Output Voltage	Dimensions
DRS24-48V-150-1050-A-NX	0.38-16.60W	24V	88%	2.5-18V	125x14x10mm
DRS24-48V-150-1050-A-NX	0.38-37.80W	48V	90%	2.5-40V	125x14x10mm

CC CE UK CA RIPPLE FREE A IP20



PCB CONVERTER DALI 24/48V

Item	Power	Input	Efficiency	Output Voltage	Dimensions
DT6-24-48V-150-1050-A-NX	0.38-16.60W	24V	88%	2.5-18V	125x14x10mm
DT6-24-48V-150-1050-A-NX	0.38-37.80W	48V	90%	2.5-40V	125x14x10mm

DALI CC CE UK CA RIPPLE FREE A IP20 PUSH DIM



PCB CONVERTER DT8 48V

Item	Power	Input	Efficiency	Output Voltage	Dimensions
DT8-48V-350-700-B-NX	0.35-0.7mA	48V	93%	3-42V	125x14x10mm

 CC CE UK CA RIPPLE FREE  PUSH DIM



POWER SUPPLY MICRO 48V

Item	Power	Output	Efficiency	Power Factor	Dimensions
LV50W48VDC-M-A-NX	0-1.05mA	48V	90%	0.95	314x19.5x27.6mm
LV100W48VDC-M-A-NX	0-2.10mA	48V	90%	0.95	314x19.5x27.6mm

CC CE UK CA RIPPLE FREE 



PCB CONVERTER MICRO ON/OFF 48V

Item	Power	Input	Efficiency	Output Voltage	Dimensions
Micro-DRS48V-100-700-NX	0.30-28.00W	48V	91%	3-40V	113.5x8x5mm

CC CE UK CA RIPPLE FREE 



PCB CONVERTER MICRO DALI 48V

Item	Power	Input	Efficiency	Output Voltage	Dimensions
Micro-DT6-48V-100-700-NX	0.30-28.00W	48V	91%	3-40V	113.5x8x3.8mm

 CC CE UK CA RIPPLE FREE  PUSH DIM



CC/CV-IOT

CC COMPACT 1CH

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC15W100-700-IOT-NFC-1CH-NX	15W	2.5-46V	86%	0.90	97x43x23mm
CC23W100-700-IOT-NFC-1CH-NX	23W	2.5-46V	87%	0.93	97x43x23mm
CC36W150-900-IOT-NFC-1CH-NX	36W	2.5-50V	88%	0.96	118x43x23mm
CC44W150-1050-IOT-NFC-1CH-NX	44W	2.5-45V	90%	0.96	118x43x23mm

CC  EAC  CE  UKCA  RoHS FREE  IP20  NFC



CC COMPACT 2CH

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC15W100-700-IOT-NFC-2CH-NX	15W	2.5-46V	85%	0.92	97x43x23mm
CC23W100-700-IOT-NFC-2CH-NX	23W	2.5-46V	87%	0.94	97x43x23mm
CC36W150-900-IOT-NFC-2CH-NX	36W	2.5-50V	88%	0.96	118x43x23mm
CC44W150-1050-IOT-NFC-2CH-NX	44W	2.5-45V	89%	0.96	118x43x23mm

CC  EAC  CE  UKCA  RoHS FREE  IP20  NFC



CV COMPACT 1CH 24/48V

Item	Power	Output	Efficiency	Power Factor	Dimensions
CV80W24CG-1CH-IOT-NX	80W	24V	90%	0.90	118x43x22.8mm
CV80W48CG-1CH-IOT-NX	80W	48V	90%	0.90	118x43x22.8mm
CV160W24CG-1CH-IOT-NX	160W	24V	92%	0.90	168x43x22.8mm
CV160W48CG-1CH-IOT-NX	160W	48V	92%	0.90	168x43x22.8mm

CV  EAC  CE  UKCA  RoHS FREE  IP20  NFC



CV COMPACT 2CH 24/48V

Item	Power	Output	Efficiency	Power Factor	Dimensions
CV80W24CG-2CH-IOT-NX	80W	24V	90%	0.90	118x43x22.8mm
CV80W48CG-2CH-IOT-NX	80W	48V	90%	0.90	118x43x22.8mm
CV160W24CG-2CH-IOT-NX	160W	24V	92%	0.90	168x43x22.8mm
CV160W48CG-2CH-IOT-NX	160W	48V	92%	0.90	168x43x22.8mm

CV  EAC  CE  UKCA  RoHS FREE  IP20  NFC



CASAMBI  matter  ZigBee  Bluetooth

CC TRACK 230V 1CH/2CH

Item	Power	Output	Efficiency	Power Factor	Dimensions
SC42W300-1050CG4-IOT-NFC-1CH-NX	42W	10-42V	90%	0.97	218x31x45mm
SC42W300-1050CG4-IOT-NFC-2CH-NX	42W	10-42V	90%	0.97	218x31x45mm



CC  EAC  UK  FREE  NFC 

CASAMBI  matter  ZigBee 

CC-INDOOR

COMPACT ON/OFF

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC21W150-500-NX	21W	20-45V	88%	0.95	97.5x44x23mm
CC30W350-700-NX	30W	27-45V	87%	0.95	97.5x44x23mm
CC44W300-1050-NX	44W	9-45V	88%	0.95	97.5x44x23mm
CC44W300-1050-NFC-NX	44W	2.5-45V	90%	0.95	97.5x44x23mm
CC44W700-1050-NX	44W	27-45V	90%	0.95	97.5x44x23mm
CC53W500-1400-NFC-NX	53W	2.5-44V	89%	0.95	97x43x30mm



CC CE EAC UK CA RIPPLE FREE IP20 PUSH DIM NFC

COMPACT DALI

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC21W150-500-DALI-NX	21W	9-45V	87%	0.97	97.5x44x23mm
CC30W350-700-DALI-NX	30W	9-45V	88%	0.97	97.5x44x23mm
CC44W300-1050-DALI-NX	44W	9-49V	88%	0.95	97.5x44x23mm
CC44W300-1050-DALI-NFC-NX	44W	2.5-45V	89%	0.95	97.5x44x23mm
CC44W700-1050-DALI-NX	44W	9-49V	88%	0.97	97.5x44x23mm
CC53W500-1400-DALI-NFC-NX	53W	2.5-44V	89%	0.95	97x43x30mm



DALI CC CE EAC UK CA RIPPLE FREE IP20 PUSH DIM CLO NFC

COMPACT HIGH EFFICIENCY

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC44W300-1050-HE-NX	44W	2.5-50V	92.5%	0.96	69x54x30mm
CC44W300-1050-NFC-HE-NX	44W	2.5-54V	92%	0.98	69x54x30mm
CC44W300-1050-DALI-HE-NX	44W	2.5-54V	92.5%	0.95	69x54x30mm
CC44W300-1050-DALI-NFC-HE-NX	44W	2.5-50V	92.5%	0.97	69x54x30mm



DALI CC CE EAC UK CA RIPPLE FREE IP20 PUSH DIM CLO NFC

COMPACT HIGH EFFICIENCY DT8

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC30W150-900-DT8-HE-NX	30W	2.5-49V	92%	0.92	97x43x30mm
CC44W300-1050-DT8-HE-NX	44W	2.5-49V	92%	0.97	97x43x30mm



DALI CC CE EAC UK CA RIPPLE FREE IP20 PUSH DIM CLO

COMPACT DT8

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC44W300-1050-DT8-NFC-NX	44W	2.5-45V	88%	0.97	97x43x30mm
CC60W700-1500-DT8-NFC-NX	60W	2.5-48V	88%	0.98	118x43x30mm




COMPACT D4i

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC30W150-900-DALI-D4i-NFC-HE-NX	30W	2.5-49V	92%	0.92	97x43x30mm
CC44W300-1050-DALI-D4i-NFC-HE-NX	44W	2.5-49V	92%	0.97	97x43x30mm



SLIM ON/OFF

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC15W100-700-NFC-NX	15W	2.5-46V	87%	0.93	104x30x21mm
CC23W100-700-NFC-NX	23W	2.5-46V	88%	0.96	104x30x21mm
CC36W150-900-NFC-NX	36W	2.5-50V	88%	0.95	128x30x21mm
CC44W150-1050-NFC-NX	44W	2.5-48V	88%	0.95	128x30x21mm



SLIM DALI

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC15W100-700-DALI-NFC-NX	15W	2.5-46V	87%	0.93	104x30x21mm
CC23W100-700-DALI-NFC-NX	23W	2.5-46V	88%	0.95	104x30x21mm
CC36W150-900-DALI-NFC-NX	36W	2.5-50V	88%	0.95	128x30x21mm
CC44W150-1050-DALI-NFC-NX	44W	2.5-48V	88%	0.95	128x30x21mm



CC-INDOOR

SLIM HIGH EFFICIENCY

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC18W100-450-HE-NX	18W	22-40V	91%	0.91	104x30x21mm
CC28W350-700-HE-NX	28W	22-40V	93%	0.94	104x30x21mm

CC CE UK CA RIPPLE FREE IP20



SLIM MINI

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC15W100-700-NFC-C38-NX	15W	2.5-46V	85%	0.93	86x30x21mm
CC15W100-700-DALI-NFC-C38-NX	15W	2.5-46V	85%	0.93	86x30x21mm
CC7W100-700-Triac-NFC-C38-NX	7W	2.5-30V	75%	0.86	86x30x21mm

DALI CC CE UK CA RIPPLE FREE IP20 TRIAC DIMMING PUSH DIM NFC CLO



ULTRA SLIM

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC15W100-700-UT-NFC-NX	15W	2.5-46V	84%	0.93	113x22x20mm
CC15W100-700-UT-DALI-NFC-NX	15W	2.5-46V	84%	0.93	113x22x20mm
CC23W100-700-UT-NFC-NX	23W	2.5-46V	87%	0.95	113x22x20mm
CC23W100-700-UT-DALI-NFC-NX	23W	2.5-46V	87%	0.95	113x22x20mm

DALI CC CE UK CA RIPPLE FREE IP20 TRIAC DIMMING PUSH DIM NFC CLO



SLIM DT8

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC15W100-700-DT8-NFC-NX	15W	2.5-46V	86%	0.91	128x30x21mm
CC23W100-700-DT8-NFC-NX	23W	2.5-46V	88%	0.95	128x30x21mm
CC36W150-900-DT8-NFC-NX	36W	2.5-46V	88%	0.95	128x30x21mm

DALI CC CE UK CA RIPPLE FREE IP20 TRIAC DIMMING PUSH DIM NFC CLO



SLIM TRIAC

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC23W150-700-TRIAC-NFC-NX	23W	6-42V	80%	0.94	128x30x21mm
CC40W150-1050-TRIAC-NFC-NX	40W	25-42V	84%	0.96	128x30x21mm

CC CE ENEC UK CR RIPPLE FREE IP20 POWER FACTOR 0.94 0.96 NPC



SLIM 0/1-10V

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC23W100-700-0-10-NX	23W	2.5-46V	87%	0.96	104x30x21mm
CC36W150-900-0-10-NX	36W	10-50V	88%	0.96	128x30x21mm
CC36W150-900-1-10-NX	36W	10-50V	88%	0.96	128x30x21mm

0...10V 1...10V CC CE ENEC EAC UK CR RIPPLE FREE IP20 POWER FACTOR 0.96 0.96 NPC



CC-INDOOR

MINI

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC7W100-700-NX	7W	2.5-20V	82%	0.85	52x29x18mm

CC CE EAC UK CA RIPPLE FREE IP20



MINI

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC20W100-800-DALI-NX	20W	3-45V	88%	0.94	75x40x21mm
CC28W100-800-NX	28W	3-46V	89%	0.94	75x40x21mm
CC20W100-800-DALI-NFC-NX	20W	3-45V	88%	0.94	75x40x21mm
CC28W100-800-NFC-NX	28W	3-46V	89%	0.94	75x40x21mm

DALI CC CE EAC UK CA RIPPLE FREE IP20 DALI CBSELV PUSH DIM CLO NFC



TINY

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC10W100-700-NFC-NX	10W	2.5-45V	85%	0.93	38x30x20mm
CC10W100-700-DALI-NFC-NX	10W	2.5-45V	82%	0.90	38x30x20mm
CC6W100-700-TRIAC-NFC-NX	6W	2.5-20V	72%	0.82	38x30x20mm
CC10W100-700-CAB-NFC-NX	10W	2.5-45V	85%	0.93	38x30x20mm
CC15W100-700P-NFC-NX	15W	2.5-45V	87%	0.96	65x40x23mm
CC15W100-700P-DALI-NFC-NX	15W	2.5-45V	86%	0.96	65x40x23mm
CC15W100-700P-CAB-NFC-NX	15W	3-45V	85%	0.95	65x40x23mm
CC23W100-700P-NFC-NX	23W	2.5-45V	87%	0.96	65x40x23mm
CC23W100-700P-DALI-NFC-NX	23W	2.5-45V	87%	0.96	65x40x23mm

CASAMBI DALI CC CE EAC UK CA RIPPLE FREE IP20 DALI CBSELV PUSH DIM CLO



ROUND

Item	Power	Output	Efficiency	Power Factor	Dimensions
RC15W100-700-NFC-NX	15W	2.5-45V	86%	0.93	Ø41x20mm
RC15W100-700-DALI-NFC-NX	15W	2.5-45V	85%	0.93	Ø41x20mm
RC6W100-700-TRIAC-NFC-NX	6W	2.5-20V	72%	0.82	Ø41x20mm
RC28W100-850-NFC-NX	28W	2.5-45V	88%	0.95	Ø54x25mm
RC28W100-850-DALI-NFC-NX	28W	2.5-45V	87%	0.95	Ø54x25mm
RC15W100-850-TRIAC-NFC-NX	15W	2.5-32V	80%	0.85	Ø54x25mm
RC36W150-1050-NFC-NX	36W	2.5-48V	89%	0.96	Ø54x25mm
RC36W150-1050-DALI-NFC-NX	36W	2.5-48V	88%	0.96	Ø54x25mm
RC23W150-1050-TRIAC-NFC-NX	23W	6-42V	83%	0.90	Ø54x25mm

DALI CC CE EAC UK CA RIPPLE FREE IP20 DALI CBSELV PUSH DIM CLO NFC





CC-LINEAR

NON-SELV DALI

Item	Power	Output	Efficiency	Power Factor	Dimensions
LC35W75-400-DALI-NFC-NX	35W	54-240V	94%	0.95	280x30x21mm
LC60W120-550-DALI-NFC-NX	60W	54-240V	94%	0.95	280x30x21mm
LC100W250-1050-DALI-NFC-NX	100W	54-240V	95%	0.95	280x30x21mm



NON-SELV FLAT 11MM

Item	Power	Output	Efficiency	Power Factor	Dimensions
LC35W75-400-DALI-NFC-F-NX	35W	54-240V	93%	0.95	361x30x11mm
LC75W150-700-DALI-NFC-F-NX	75W	54-240V	94%	0.98	361x30x11mm



NON-SELV

Item	Power	Output	Efficiency	Power Factor	Dimensions
LC20W200-350NS-NX	20W	24-105V	89%	0.95	165x30x21mm
LC40W200-350NS-NX	40W	40-200V	93%	0.95	165x30x21mm
LC60W200-350NS-NX	60W	40-220V	93%	0.95	165x30x21mm
LC80W350-500NS-NX	80W	40-230V	94%	0.95	195x30x21mm
LC100W350-500NS-NX	100W	40-220V	94%	0.95	230x30x21mm
LC150W550-700NS-NX	150W	40-220V	95%	0.95	230x30x21mm



SELV ON/OFF

Item	Power	Output	Efficiency	Power Factor	Dimensions
LC35W150-700-NFC-NX	35W	20-55V	89%	0.96	280x29.4x21mm
LC50W300-1050-NFC-NX	50W	20-50V	90%	0.96	280x29.4x21mm
LC75W900-1800-NFC-NX	75W	20-50V	91%	0.96	280x29.4x21mm



SELV DALI

Item	Power	Output	Efficiency	Power Factor	Dimensions
LC35W150-700-DALI-NFC-NX	35W	20-55V	89%	0.95	280x30x21mm
LC50W300-1050-DALI-NFC-NX	50W	20-50V	89%	0.95	280x30x21mm
LC75W900-1800-DALI-NFC-NX	75W	20-50V	89%	0.95	280x30x21mm



SELV FLAT 11MM ON/OFF

Item	Power	Output	Efficiency	Power Factor	Dimensions
LC35W150-700-NFC-F-NX	35W	20-50V	87%	0.95	360x30x11mm
LC50W300-1050-NFC-F-NX	50W	20-50V	88%	0.95	360x30x11mm
LC75W900-1800-NFC-F-NX	75W	20-50V	89%	0.95	360x30x11mm



SELV FLAT 11MM DALI

Item	Power	Output	Efficiency	Power Factor	Dimensions
LC35W150-700-DALI-NFC-F-NX	35W	20-50V	86%	0.95	360x30x11mm
LC50W300-1050-DALI-NFC-F-NX	50W	20-50V	87%	0.95	360x30x11mm
LC75W900-1800-DALI-NFC-F-NX	75W	20-50V	88%	0.95	360x30x11mm



SELV DT8

Item	Power	Output	Efficiency	Power Factor	Dimensions
LC35W150-700-DT8-NFC-NX	35W	20-50V	89%	0.95	280x30x21mm
LC50W300-1050-DT8-NFC-NX	50W	20-50V	89%	0.95	280x30x21mm
LC75W900-1800-DT8-NFC-NX	75W	20-50V	89%	0.95	360x30x21mm



CC-UNI 100-240V

TINY

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC9W100-700P-NFC-UNI-NX	9W	2.5-45V	88%	0.96	65x40x23mm
CC9W100-700P-DALI-NFC-UNI-NX	9W	2.5-45V	87%	0.96	65x40x23mm













SLIM

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC14W100-700-NFC-UNI-NX	14W	2.5-46V	87%	0.90	103.4x30x21mm
CC14W100-700-DALI-NFC-UNI-NX	14W	2.5-46V	87%	0.93	103.4x30x21mm
CC22W150-900-NFC-UNI-NX	22W	2.5-50V	88%	0.98	128x30x21mm
CC22W150-900-DALI-NFC-UNI-NX	22W	2.5-50V	88%	0.95	128x30x21mm













MINI

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC17W100-800-UNI-NX	17W	3-46V	89%	0.94	75x40x21mm
CC12W100-800-DALI-UNI-NX	12W	3-45V	88%	0.94	75x40x21mm












COMPACT

Item	Power	Output	Efficiency	Power Factor	Dimensions
CC25W300-1050-NFC-UNI-NX	25W	9-45V	88%	0.95	98x44x23mm
CC25W300-1050-DALI-NFC-UNI-NX	25W	9-45V	88%	0.95	98x44x23mm
CC32W650-1400-NFC-UNI-NX	32W	2.5-44V	90%	0.98	97x43x23mm
CC32W650-1400-DALI-NFC-UNI-NX	32W	2.5-44V	90%	0.98	97x43x23mm















CV-INDOOR

LINEAR ON/OFF 24V

Item	Power	Output	Efficiency	Power Factor	Dimensions
LV40W24CG-NX	40W	24V	88%	0.95	300x30x16mm
LV75W24CG-NX	75W	24V	89%	0.95	350x30x18mm
LV120W24CG-NX	120W	24V	93%	0.95	350x30x18mm
LV160W24CG-NX	160W	24V	93%	0.95	350x30x18mm
LV200W24CG-NX	200W	24V	93%	0.95	400x40x22mm
LV250W24CG-NX	250W	24V	93%	0.95	400x40x22mm

CV CE UK CA RIPPLE FREE IP20 PUSH DIM



LINEAR DALI

Item	Power	Output	Efficiency	Power Factor	Dimensions
LV40W24CG-DALI-NX	40W	24V	87%	0.95	300x30x16mm
LV75W24CG-DALI-NX	75W	24V	88%	0.95	350x30x18mm
LV120W24CG-DALI-NX	120W	24V	92%	0.95	350x30x18mm
LV160W24CG-DALI-NX	160W	24V	92%	0.95	350x30x18mm
LV200W24CG-DALI-NX	200W	24V	92%	0.95	400x40x22mm
LV250W24CG-DALI-NX	250W	24V	92%	0.95	400x40x22mm

DALI CV CE UK CA RIPPLE FREE IP20 PUSH DIM



LINEAR DT8 24V

Item	Power	Output	Efficiency	Power Factor	Dimensions
LV40W24CG-DT8-NX	40W	24V	87%	0.95	300x30x16mm
LV75W24CG-DT8-NX	75W	24V	88%	0.95	350x30x18mm
LV120W24CG-DT8-NX	120W	24V	92%	0.95	400x40x22mm
LV160W24CG-DT8-NX	160W	24V	92%	0.95	400x40x22mm
LV200W24CG-DT8-NX	200W	24V	92%	0.95	400x40x22mm
LV250W24CG-DT8-NX	250W	24V	92%	0.95	400x40x22mm

DALI CV CE UK CA RIPPLE FREE IP20 PUSH DIM



LINEAR ON/OFF 48V

Item	Power	Output	Efficiency	Power Factor	Dimensions
LV40W48CG-NX	40W	48V	88%	0.95	300x30x16mm
LV75W48CG-NX	75W	48V	89%	0.95	350x30x18mm
LV120W48CG-NX	120W	48V	93%	0.95	350x30x18mm
LV160W48CG-NX	160W	48V	93%	0.95	350x30x18mm
LV200W48CG-NX	200W	48V	93%	0.95	400x40x22mm
LV250W48CG-NX	250W	48V	93%	0.95	400x40x22mm

CV CE UK CA RIPPLE FREE IP20 PUSH DIM



LINEAR DALI 48V

Item	Power	Output	Efficiency	Power Factor	Dimensions
LV40W48CG-DALI-NX	40W	48V	87%	0.95	300x30x16mm
LV75W48CG-DALI-NX	75W	48V	88%	0.95	350x30x18mm
LV120W48CG-DALI-NX	120W	48V	92%	0.95	350x30x18mm
LV160W48CG-DALI-NX	160W	48V	92%	0.95	350x30x18mm
LV200W48CG-DALI-NX	200W	48V	92%	0.95	400x40x22mm
LV250W48CG-DALI-NX	250W	48V	92%	0.95	400x40x22mm



DALI CV CE UK CA RIPPLE FREE IP20 PUSH DIM

LINEAR DT8 48V

Item	Power	Output	Efficiency	Power Factor	Dimensions
LV40W48CG-DT8-NX	40W	48V	87%	0.95	300x30x16mm
LV75W48CG-DT8-NX	75W	48V	88%	0.95	350x30x18mm
LV120W48CG-DT8-NX	120W	48V	92%	0.95	400x40x22mm
LV160W48CG-DT8-NX	160W	48V	92%	0.95	400x40x22mm
LV200W48CG-DT8-NX	200W	48V	92%	0.95	400x40x22mm
LV250W48CG-DT8-NX	250W	48V	92%	0.95	400x40x22mm



DALI CV CE UK CA RIPPLE FREE IP20 PUSH DIM

COMPACT ON/OFF

Item	Power	Output	Efficiency	Power Factor	Dimensions
CV30W24CG-NX	30W	24V	87%	0.95	135x36x25mm
CV60W24CG-NX	60W	24V	89%	0.95	151.5x40.2x31mm
CV120W24CG-NX	120W	24V	94%	0.95	253x42.5x31mm
CV180W24CG-NX	180W	24V	94%	0.95	253x42.5x31mm
CV250W24CG-NX	250W	24V	95%	0.95	270x50x31mm



30W AND 60W ALSO AVAILABLE IN 12V

CV CE UK CA RIPPLE FREE IP20

COMPACT DALI

Item	Power	Output	Efficiency	Power Factor	Dimensions
CV30W24CG-DALI-NX	30W	24V	90%	0.92	135x36x25mm
CV60W24CG-DALI-NX	60W	24V	92.5%	0.95	151.5x40.2x31mm
CV120W24CG-DALI-NX	120W	24V	93%	0.95	253x42.5x31mm
CV180W24CG-DALI-NX	180W	24V	93%	0.95	253x42.5x31mm
CV250W24CG-DALI-NX	250W	24V	94%	0.95	270x50x31mm



DALI CV CE UK CA RIPPLE FREE IP20 PUSH DIM

CV-INDOOR

ROUND 12/24/48V

Item	Power	Output	Efficiency	Power Factor	Dimensions
RV24W12-NX	24W	12V	85%	0.95	Ø55x25mm
RV25W24-NX	25W	24V	86%	0.95	Ø55x25mm
RV25W48-NX	25W	48V	86%	0.95	Ø55x25mm

CV CE EAC UK CA RIPPLE FREE IP20



LINEAR 24V

Item	Power	Output	Efficiency	Power Factor	Dimensions
LV36W24-NX	36W	24V	83%	0.90	165x30x21mm
LV36W24-DALI-NX	36W	24V	88%	0.95	165x30x21mm
LV60W24-NX	60W	24V	91%	0.95	230x30x21mm
LV60W24-DALI-NX	60W	24V	87%	0.95	230x30x21mm
LV100W24-NX	100W	24V	91%	0.95	360x30x21mm
LV100W24-DALI-NX	100W	24V	92%	0.95	360x30x21mm
LV150W24-NX	150W	24V	92%	0.95	360x30x21mm
LV150W24-DALI-NX	150W	24V	92%	0.95	360x30x21mm

DALI CV CE UK CA RIPPLE FREE IP20 PUSH DIM



COMPACT TRIAC

Item	Power	Output	Efficiency	Power Factor	Dimensions
CV25W24CG-Triac-NX	25W	24V	85%	0.95	128x52x30mm
CV50W24CG-Triac-NX	50W	24V	86%	0.95	184x61x32mm
CV100W24CG-Triac-NX	100W	24V	91%	0.95	210x67x34mm
CV150W24CG-Triac-NX	150W	24V	89%	0.95	210x67x34mm

CV CE UK CA RIPPLE FREE IP20



SLIM 24/48V

Item	Power	Output	Efficiency	Power Factor	Dimensions
CV24W24-NX	24W	24V	85%	0.95	128x30x21mm
CV24W24-DALI-NX	24W	24V	84%	0.95	128x30x21mm
CV24W48-NX	24W	48V	86%	0.95	128x30x21mm
CV24W48-DALI-NX	24W	48V	85%	0.95	128x30x21mm

DALI CV CE UK CA RIPPLE FREE IP20 PUSH DIM





CC/CV-OUTDOOR

CC COMPACT ON/OFF

Item	Power	Output	Efficiency	Power Factor	Dimensions
XSC23W100-700-NFC-NX	23W	2.5-46V	87%	0.94	75x45.2x25.2mm
XSC44W300-1050-NFC-NX	44W	2.5-45V	89%	0.96	95x45.2x25.1mm
XSC70W350-1400-NFC-NX	70W	2.5-48V	91%	0.95	95x65.2x25mm

CC CE EAC UK CR RIPPLE FREE IP67 NPC



CC COMPACT DALI

Item	Power	Output	Efficiency	Power Factor	Dimensions
XSC23W100-700-DALI-NFC-NX	23W	2.5-46V	87%	0.94	75x45.2x25.2mm
XSC44W300-1050-DALI-NFC-NX	44W	2.5-46V	89%	0.96	95x45.2x25.1mm
XSC70W350-1400-DALI-NFC-NX	70W	10-50V	89%	0.95	95x65.2x25.1mm

DALI CC CE EAC UK CR RIPPLE FREE IP67 PUSH DIM NPC



CV SLIM ON/OFF 24V

Item	Power	Output	Efficiency	Power Factor	Dimensions
XSV30W24-NX	30W	24V	86%	0.95	235x30x21mm
XSV60W24-NX	60W	24V	88%	0.95	275x30x21mm
XSV100W24-NX	100W	24V	90%	0.95	305x30x21mm
XSV160W24-NX	160W	24V	92%	0.95	335x30x21mm
XSV240W24-NX	240W	24V	92%	0.95	385x30x21mm
XSV400W24-NX	400W	24V	93%	0.95	385x60x22mm

CV CE EAC UK CR RIPPLE FREE IP67



CV SLIM DALI 24V

Item	Power	Output	Efficiency	Power Factor	Dimensions
XSV30W24-DALI-NX	30W	24V	86%	0.95	235x30x21mm
XSV60W24-DALI-NX	60W	24V	88%	0.95	275x30x21mm
XSV100W24-DALI-NX	100W	24V	90%	0.95	305x30x21mm
XSV160W24-DALI-NX	160W	24V	92%	0.95	335x30x21mm
XSV240W24-DALI-NX	240W	24V	92%	0.95	385x30x21mm
XSV400W24-DALI-NX	400W	24V	93%	0.95	385x60x22mm

DALI CV CE EAC UK CR RIPPLE FREE IP67 PUSH DIM



CV SLIM ON/OFF 48V

Item	Power	Output	Efficiency	Power Factor	Dimensions
XSV60W48-NX	60W	48V	88%	0.95	275x30x21mm
XSV100W48-NX	100W	48V	90%	0.95	305x30x21mm
XSV160W48-NX	160W	48V	92%	0.95	335x30x21mm
XSV240W48-NX	240W	48V	92%	0.95	385x30x21mm
XSV400W48-NX	400W	48V	93%	0.95	380x60x22mm

CV CE UK CA RIPLE FREE & IP67



CV SLIM DALI 48V

Item	Power	Output	Efficiency	Power Factor	Dimensions
XSV60W48-DALI-NX	60W	48V	88%	0.95	275x30x21mm
XSV100W48-DALI-NX	100W	48V	90%	0.95	305x30x21mm
XSV160W48-DALI-NX	160W	48V	92%	0.95	335x30x21mm
XSV240W48-DALI-NX	240W	48V	92%	0.95	385x30x21mm
XSV400W48-DALI-NX	400W	48V	93%	0.95	380x60x22mm

DALI CV CE UK CA RIPLE FREE & IP67 PUSH DIM



COMPACT UNI 12/24V

Item	Power	Output	Efficiency	Power Factor	Dimensions
XV36W24-UNI-NX	36W	24V	85%	0.60	148x40x30mm
XV60W12-UNI-NX	60W	24V	85%	0.90	166x42x34mm
XV100W12-UNI-NX	100W	24V	84%	0.90	190x52x37mm
XV150W24-UNI-NX	150W	24V	88%	0.60	190x63x38mm

ALSO AVAILABLE IN 12V

DALI CV CE UK CA RIPLE FREE & IP67 PUSH DIM



NEX·IVO

— by KGP Electronics GmbH —

Hueckstr. 19 · 58511 Lüdenscheid, Germany

Phone: +49 (0) 2351 . 67 21 00

Email: info@kgp-electronics.de

www.kgp-electronics.de

Visit us 



Follow us 

